



Modos Operación:

- Modo Enfriamiento en 2 Pasos (Fast Cool - Confort Cool)
- Modo Enfriamiento Rápido
- Modo Good Sleep
- Modo Deshumidificador

Beneficios:

- Digital Inverter
- Estabilizador de Voltaje Incorporado
- Filtro Aire 80% Eficiencia
- Sistema Spi-Doctor Virus 99.9% Eficiencia (Elimina AH1N1)
- Auto Restart



Model Code		AR09KVSSCWK/CB	AR12KVSSCWK/CB	AR18KVSSCWK/CB	AR24KVSSCWK/CB
Capacity	Capacity (Cooling, Btu/hr)	9000 Btu/hr	11000 Btu/hr	16500 Btu/hr	20000 Btu/hr
	Capacity (Heating, Btu/hr)	- Btu/hr	- Btu/hr	- Btu/hr	- Btu/hr
	Capacity (Cooling, Min - Max, Btu/hr)	5200~11000 Btu/hr	4026~13648 Btu/hr	4777~21154 Btu/hr	5016~28149 Btu/hr
	Capacity (Heating, Min - Max, Btu/hr)	- Btu/hr	- Btu/hr	- Btu/hr	- Btu/hr
	Capacity (Cooling, kW)	2.64 kW	3.22 kW	4.84 kW	5.86 kW
	Capacity (Heating, kW)	- kW	- kW	- kW	- kW
	Capacity (Cooling, Min - Max, kW)	1.52~3.22 kW	1.18~4.0 kW	1.4~6.2 kW	1.47~8.25 kW
	Capacity (Heating, Min - Max, kW)	- kW	- kW	- kW	- kW
	Capacity (Cooling, Kcal/hr)	2268 Kcal/hr	2773 Kcal/hr	4159 Kcal/hr	5041 Kcal/hr
Capacity (Heating, Kcal/hr)	- Kcal/hr	- Kcal/hr	- Kcal/hr	- Kcal/hr	
Energy Efficiency	EER (Cooling, W/W)	3.340 W/W	3.341 W/W	3.410 W/W	3.338 W/W
	COP (Heating, W/W)	- W/W	- W/W	- W/W	- W/W
	EER (Cooling, Btu/hW)	11.39 Btu/hW	11.40 Btu/hW	11.62 Btu/hW	11.40 Btu/hW
	Energy Efficiency Class for cooling (Grade)	C	C	C	C
Noise Level	Noise Level (Indoor, High/Low, dBA)	37/20 dBA	37/20 dBA	42/26 dBA	44/30 dBA
	Noise Level (Outdoor, High/Low, dBA)	49 dBA	48 dBA	52 dBA	54 dBA
Electrical Data	Power Source(Φ/V/Hz)	220 / 60 / 1 (B)	220 / 60 / 1 (B)	220 / 60 / 1 (B)	220 / 60 / 1 (B)
	Power Consumption(Cooling, W)	790 W	965 W	1420 W	1755 W
	Power Consumption(Heating, W)	- W	- W	- W	- W
	Operating Current(Cooling, A)	4 A	5 A	6.7 A	8.5 A
	Operating Current(Heating, A)	- A	- A	- A	- A
Physical specification	Net Dimension (Indoor, WxHxD, mm*mm*mm)	826*261*261 mm	826*261*261 mm	1065*301*294 mm	1065*301*294 mm
	Net Dimension (Outdoor, WxHxD, mm*mm*mm)	660*475*242 mm	720*548*265 mm	790*548*285 mm	880*638*310 mm
	Gross Weight (Indoor, kg)	11.2 kg	11.2 kg	15.0 kg	15.0 kg
	Gross Weight (Outdoor, kg)	21.5 kg	29.0 kg	36.5 kg	46.5 kg
	Net Weight (Indoor, kg)	9.8 kg	9.8 kg	13.0 kg	13.0 kg
Net Weight (Outdoor, kg)	19.0 kg	26.0 kg	32.7 kg	41.5 kg	
Technical Information	Piping Length (Max, m)	15 m	15 m	30 m	30 m
	Piping Height (Max, m)	7 m	7 m	15 m	15 m
	SVC Valve (Liquid (ODxL))	6.35	6.35	6.35	6.35
	SVC Valve (Gas (ODxL))	9.52	9.52	12.70	15.88
	Low Ambient (Cooling, °C)	16~46 °C	16~46 °C	16~46 °C	16~46 °C
	Low Ambient (Heating, °C)	- °C	- °C	- °C	- °C
	Outdoor Unit (Compressor Type)	BLDC ROTARY	BLDC ROTARY	BLDC ROTARY	BLDC ROTARY
	Outdoor Unit (Anti-Corrosion Fin)	Yes	Yes	Yes	Yes
Air Flow	Air Direction Control (Up/Down)	Auto	Auto	Auto	Auto
	Air Direction Control (Left/Right)	Manual	Manual	Manual	Manual
	Air Flow Control Step (Cool/Fan)	5/4	5/4	5/4	5/4
Air Purification	Auto Clean (Self Cleaning)	Yes	Yes	Yes	Yes
Convenience	Indoor Temp. Display	No	No	No	No
	Display On/Off	No	No	No	No
	Beep On/Off	Yes	Yes	Yes	Yes
	Auto Restart	Yes	Yes	Yes	Yes
Operating Mode	2 Step Cooling	Yes	Yes	Yes	Yes
	Fast Cool	Yes	Yes	Yes	Yes
	Good Sleep	Yes	Yes	Yes	Yes
	Single User Mode	Yes	Yes	Yes	Yes
	Dehumidification	Yes	Yes	Yes	Yes
	Fan Mode	Yes	Yes	Yes	Yes
	Quiet	Yes	Yes	Yes	Yes