



CONFORTFRESH®
AIR CONDITIONING



EQUIPO DESHUMIDIFICADOR CONFORTFRESH®

Especificaciones técnicas

Product Model			MDCK-60AEN1	MDCK-70AEN1
Power supply	Voltage type		115V,1Ph	115V,1Ph
	Supply frequency		60Hz	60Hz
Control type	Moisture removal (US)	Pints/Day	60	70
	Control type		[Electronic Control]	[Electronic Control]
System data	Air flow (Hi)	m3/h	320	320
	Air flow (Lo)	m3/h	280	280
	Front side sound pressure level(Hi)	dB(A)	56	56
	Front side sound pressure level(Lo)	dB(A)	54	54
	Rear side sound pressure level(Hi)	dB(A)	51.5	53
	Standby power consumption	W	3	
Applicable ambient	Water tank volume	L	6	6
	RH Range manual	%	35-85	35-85
	Ambient temp		5-35	5-35
Application area	Applicable_aera_Min	m2	55	65
	Applicable_aera_Max	m2	70	80
Refrigerant	Refrigerant type		R410A	
	Refrigerant charge	onz	7.58	8.29
Dimension(W*D*H)	Body_Length(W)	mm	391	
	Body_Width(D)	mm	275	
	Body_Height(H)	mm	590	
Packing(W*D*H)	Packing_Length(W)	mm	422	
	Packing_Width(D)	mm	312	
	Packing_Height(H)	mm	632	

Especificaciones y modelos sujetos a cambio sin previo aviso.

*Dimensiones: Largo / Alto / Profundidad
Imágenes de referencia sujetas a cambio.